



Q

Fig.1




Fig.2





Fig.3



テーパ	Code No.	Q	L	C	C1	H	H1	接続ボルト No.	Fig.	重量(kg)
HSK 40A	HSK 40A-Q26- 75	26	75	50	33.6	55	40	B26N	3	0.8
HSK 50A	HSK 50A-Q26- 75	26	75	50	41.6	48	33	B26N	3	1.1
HSK 63A	HSK 63A-Q 9- 80	9	80	19	30	49	5	B19	2	0.7
	- 95N		95			64	27			0.7
	-Q12- 80	12	80	24	35	49	12	B12	2	0.8
	-110		110			79	50			0.8
	-Q16- 95	16	95	31	42	64	22	B16	2	1.0
	-125		125			94	55			1.1
	-Q20- 80	20	80	40	50	53	27	B20	2	1.4
	-110		110			83	60			1.3
	-Q26- 60	26	60	50	—	33	—	B26N	1	1.0
	- 95		95			68	—			1.5
	-140		140			113	—			2.3
	-Q34- 95	34	95	64	52.4	68	53	B34	3	2.0
	-110		110			83	68			2.4
-Q42- 95	42	95	83	52.4	68	35	B42	3	2.5	
HSK100A	HSK100A-Q 9-110	9	110	19	40	76	5	B19	2	2.3
	-125N		125			91	27			2.3
	-Q12- 95	12	95	24	44	61	12	B12	2	2.3
	-125		125			91	50			2.3
	-Q16-125N	16	125	31	50	91	22	B16	2	2.8
	-155		155			121	55			2.9
	-Q20-110	20	110	40	60	76	27	B20	2	3.0
	-125		125			91	60			2.9
	-Q26- 65	26	65	50	65	33	—	B26N	1	2.4
	-140		140			106	45		2	4.5
	-170N		170			136	110		4.6	
	-Q34-140	34	140	64	80	106	—	B34	1	4.4
	-170		170			138	117		2	5.3
	-200		200			168	147		5.9	
	-Q42-125	42	125	83	—	95	—	B42	1	5.3
	-190		190			160	7.9			
	-Q42-225A	42	225	83	—	—	—	B42	1	11.7
-275A	275		—			—	14.4			
-325A	325		—			—	17.1			
-375A	375		—			—	19.8			

- ★全シリーズスルーホール付きです。
- ★接続ボルト及びレンチは付属しています。
- ★クーラントパイプは別売りです。P.287を参照下さい。
- ★標準よりL寸法が長い場合、有効ボアリング長MとQ No.をご指定下さい。

